

# ValueJet

ValueJet VJ-628



## Compact 24" Wide Desktop Eco Ultra Printer

The VJ-628 is Mutoh's smallest sign & display printer offering a great potential to startup businesses, small sign makers, department stores and quick print providers. Offering a media width of 630 mm (24"), the compact, user-friendly & cost-effective ValueJet 628 has been developed for a wide array of applications ranging from in-store printing, commercial print, signage and print-to-cut applications.



Equipped with a latest generation micro piezo print head, this compact 8 channel desktop printer delivers high quality prints for indoor & outdoor applications.

### Product Highlights

- Powerful 8 channel desktop printer
- Latest generation piezo print head technology on board
- Impeccable print quality every time with Mutoh Intelligent Interweaving print technology (i<sup>2</sup>)
- Durable graphics with Mutoh Eco Ultra inks
- Production speed range from 3 to 12.5 m<sup>2</sup>/h

### Application Possibilities

Designed for small-lot on demand production, the VJ-628 is suited for a wide variety of outdoor and indoor prints : long-term outdoor posters, stickers & labels, signs and banners, apparel decoration, backlit signage, POS displays, vehicle & window graphics, photo prints, fine art reproduction, etc..



# MUTOH

Mutoh Belgium - [www.mutoh.eu](http://www.mutoh.eu) / Mutoh Deutschland - [www.mutoh.de](http://www.mutoh.de)  
Mutoh North Europe - [www.mutohnorth.eu](http://www.mutohnorth.eu)



ValueJet VJ-628



## 24" Sign & Display Printer

## SPECIFICATIONS

### Technical Key Specifications

Print Technology	Drop-on-demand Micro Piezo Inkjet Technology
Print Head	1 (8 colour channels)
Nozzle Configuration	180 nozzles x 8 lines
Drop Mass Range (pl)	3,5 to 35,2
Head Heights	Low: 1.2 mm / High: 2.5 mm

### Media Specifications

Max. Media Width	630 mm (24,80")
Max. Print Width	620 mm (24,40")
Max. Media Thickness	0.3 / 1.3 mm *
*: Max. media thickness is specified per head height	
Media Measurements *	Ø 150 mm / 2" & 3" / 9 kg
*: Standard non-motorised roll-off system	
Media Drying System	3 heater zones: pre-heater, platen heater and after heater. Single control : off, 30-45 °C
Sheet Off Function	Automatic sheet off system integrated

### Ink Specifications

Ink Type	Eco Ultra
Ink Volume	220 ml c assette / 1000 ml bag *
*: 1 L bag requires optional adapter	
Ink Colours	CMYK
Ink Consumption *	8 ml / m <sup>2</sup>
*: Average ink consumption at @720 dpi - coverage of 67 %	
UV durability — without lamination	3 years outdoor *
*: For heavy duty applications where mechanical stress is involved, lamination is required. Stabilisation is required prior to lamination.	

### Machine Measurements

Width x Depth x Height	1190 x 437,5 x 365,6 mm (Desktop) 1190 x 590 x 1165,6 mm (+ Optional stand)
Weight Desktop / Stand	31.8 kg / 40.5 kg

### Performance

High Quality (720 x 1080)	3.0 m <sup>2</sup> /h
Quality (720 x 720)	4.6 m <sup>2</sup> /h
Quality Production (720 x 1080)	5.9 m <sup>2</sup> /h
Production (720 x 720)	9.0 m <sup>2</sup> /h
Speed Production (720 x 720)	12.5 m <sup>2</sup> /h
Billboard (360 x 720)	16 m <sup>2</sup> /h

\* All speeds indicated for 4 colour setup. Full width.  
Intelligent Interweaving active

### Power Consumption

During Printing	≤ 830 W
Power Supply	AC 100-120 V / AC 200-240 - 60/50 Hz - ≤ 6.5 A / ≤ 3.5 A

### Recommended Working Environment

Temperature	20 °C - 32 °C with ΔΔ max. 2 °C/h
Humidity	40 % - 60 % (no condensation) with ΔRH: max. 5 % RH/h

Distributed by:



info@plot-it.co.uk | 0844 847 9795

[www.plot-it.co.uk](http://www.plot-it.co.uk)